

**121L8807****Scroll compressor, MLZ048T2LQ9A**

Refrigerants: R404A; R407C; R507A; R452A; R134a; R513A; R22; R448A; R449A,
Segment usage: Refrigeration HT; Refrigeration MT, Compressor power supply [V]:
200-220/3/50 208-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	42.31 Kilogram
Net weight	37.2 Kilogram
Volume	0.1 Cubic meter
EAN	5702424059453
Approval	CE UKCA UL
Brand technique	Scroll compressor
Capacity control	Fixed speed
CE evaluated	Yes
China RoHS compliance	Yes exceed limitations
Colour	Blue
Compressor power supply [V]	200-220/3/50 208-230/3/60
Configuration code	Single
Connection type	Rotolock
Description	MLZ048T2A
Diameter [mm]	184 mm
Discharge connection height [mm]	422 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	0XR6298B-3
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	7(c)-I 6(a) 6(a)-I 6(c) 7(a) 8(b)
Family	MLZ
Fitting standard	Rotolock
Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	None
Glass mounting	Threaded
Glass torque [Nm]	53 N-m
High value of nominal voltage at 50Hz [V]	220 V

Product Detail | Scroll compressor, MLZ048T2LQ9A

PRODUCT DETAILS

High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 50Hz [V]	242 V
High value of voltage range at 60Hz [V]	253 V
In scope of WEEE and contain batteries	No
IP protection class	IP22
Liquid injection	No
Low value of nominal voltage at 50Hz [V]	200 V
Low value of nominal voltage at 60Hz [V]	208 V
Low value of voltage range at 50Hz [V]	180 V
Low value of voltage range at 60Hz [V]	187 V
LRA	190 A
Max pressure (PS) - high side	31.1 bar
Max pressure (PS) - low side	26.2 bar
MCC	37 A
Model number	MLZ048T2LQ9A
Motor protection	Internal overload protector
Network power supply [V/Ph/Hz]	200-230/3/50 208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.57 L
Oil drain	1/4" flare
Oil equalization	None
Oil reference	215PZ
Oil type	POE
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Screw connectors 10-32 UNF x 9.5
Product group	Hermetic compressors
Product Name Description	Scroll compressor MLZ
Refrigerant charge [kg] [Max]	5.44 kg
Refrigerants	R134a R22 R404A R407C R448A R449A R452A R507A R513A
RLA	23.7 A
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Refrigeration MT Refrigeration HT
Suction connection height [mm]	280 mm

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Scroll compressor, MLZ048T2LQ9A
PRODUCT DETAILS

Suction connection material	-
Suction connection pipe size [in]	7/8 in
Suction connection size [in]	1 1/4 in
Swept volume [cm³]	107.48 cm ³
Technology	Scroll
Torque earth [Nm]	2 N-m
Torque power [Nm]	3 N-m
Total height [mm]	455 mm
Type	MLZ048A
U.S. EPA label	For installations using U.S. EPA restricted refrigerants, this product may be used for servicing existing equipment only.
UK RoHS compliance	Yes with exemptions
UK RoHS exemption clause	19 21 24 12 13 18
UL evaluated	Yes
Viscosity [cP]	46 cP
Voltage of capacitor A [V]	370 V
Winding resistance 1-2 [Ohm]	0.44
Winding resistance 1-3 [Ohm]	0.43
Winding resistance 2-3 [Ohm]	0.43

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

8156009 [↗](#)
Connector, Gasket

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white


8156131 [↗](#)
Connector, Gasket

Gasket, 1-1/4"

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts



120Z0059 [🔗](#)

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 230 V



8168030 [🔗](#)

Connector, Rotolock service valve

Rotolock valve, V05 (1-1/4" rotolock, 7/8" ODF)



120Z0892 [🔗](#)

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 230 V



8168029 [🔗](#)

Connector, Rotolock service valve

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.